



AQ20

AlfaQ™ ARI-certified plate heat exchanger

Applications

General heating and cooling duties.

Standard design

The plate heat exchanger consists of a pack of corrugated metal plates with portholes for the passage of the two fluids between which heat transfer will take place.

The plate pack is assembled between a fixed frame plate and a movable pressure plate and compressed by tightening bolts. The plates are fitted with a gasket which seals the interplate channel and directs the fluids into alternate channels. The number of plates is determined by the flow rate, physical properties of the fluids, pressure drop and temperature program. The plate corrugations promote fluid turbulence and support the plates against differential pressure.

The frame plate and the pressure plate are suspended from an upper carrying bar and located by a lower guiding bar, both of which are fixed to a support column.

Connections are located in the frame plate or, if either or both fluids make more than a single pass within the unit, in the frame and pressure plates.


Typical capacities

Liquid flow rate

Up to 15,500 GPM (975 kg/s), depending on media, permitted pressure drop and temperature program.

Frame types

FG and FD



AQ20-FG

Working principle

Channels are formed between the plates and the corner ports are arranged so that the two media flow through alternate channels. The heat is transferred through the plate between the channels, and complete counter-current flow is created for highest possible efficiency. The corrugation of the plates provides the passage between the plates, supports each plate against the adjacent one and enhances the turbulence, resulting in efficient heat transfer.

Standard Materials

Frame plate

Mild steel, painted

Nozzles

Carbon steel

Metal-lined: Stainless steel, Titanium

Plates

Stainless steel: Alloy 316, Titanium

Gaskets

Nitrile or EPDM

Connections

FG – Size 20" ASME Cl. 150

FS – Size 20" ASME Cl. 300

Technical Data

Mechanical design pressure/temperature

FG – ASME 150 psig/200°F

FD – ASME 300 psig/200°F


Maximum heat transfer surface

2880 m² (31018 sq. ft)

ALFA LAVAL is a registered trademark of Alfa Laval Corporate AB




A Participating Company in the
ARI Standard 400 Certification Program



Flow principle of a plate heat exchanger

Dimensions



Measurements millimeters (in)

Type	H	W	h
AQ20-FG	3951 (155 9/16")	1550 (61")	467 (18 3/8")
AQ20-FD	3951 (155 9/16")	1550 (61")	467 (18 3/8")

The number of tightening bolts may vary depending on pressure rating.

Particulars required for quotation

- Flow rates or heat load
- Temperature program
- Physical properties of liquids in question (if not water)
- Desired working pressure
- Maximum permitted pressure drop
- Available steam pressure

How to contact Alfa Laval

Contact details for all countries
are continually updated on our website.
Please visit www.alfalaval.us
to access the information directly.